

High-pressure autoclave «sonar» with full-length inspection window

At last – the «sonar» has arrived! premex reactor ag now presents a high-pressure autoclave with a full-length inspection window – and it can cope with pressures up to an incredible 150 bar! Now you can also follow the reaction visually as it proceeds. You will not only be convinced by this product's technical details, but also by its extremely compact design.

Basic information	
Nominal volume	300 ml
Excess operating pressure	150 bar
Operating temperature	200°C
Material	Mat. no. 1.4435 (AISI 316L)

Dimensions	
Internal vessel diameter, 60x145 mm; total height including magnetic stirrer, approx. 600 mm	

Autoclave lock	
Jaw lock (fast closing system)	

Autoclave seal	
Viton O-ring	

Magnetic stirrer drive	
Type «mini», magnetic coupling torque: 50 Ncm, electrical motor with nominal power 40 Watt, 3x230/400 V, 50 Hz.	

Fittings on the «mini»	
1. Whitey gas supply valve 2. Manometer 0–160 bar, ø 40 mm	

Fittings on the autoclave cover	
1. Temperature sensor, Pt 100 (1x) 2. Sapphire window to light the vessel 3. Bore hole for pressure release with Whitey valve 4. Nupro spring pressure safety valve 5. Bore hole with plug	

Base outlet	
Whitey ball valve, type SS-43XS6MM	

Base form	
Conical outlet, 10°C. Frit can be fitted.	

Inspection window	
Inspection window running the whole length of the cylinder, inner width 10 mm, made of dual glass.	

Stirrers	
Gasification stirrers, or other stirrers.	

Heating / cooling	
Double shell heating, welded structure, insulated all round and clad with a CN shell. Internal guide plates are used to direct the oil. The outer shell of the autoclave vessel has two connectors for forward/reverse heat transfer oil flow. Alternatively, premex reactor ag offers the «sonar» autoclave with electrical heating.	

Structural design	
Three adjustable supporting legs on the base plate of the autoclave provide sufficient floor clearance for the outlet valve to be operated.	

hpm-s

phone	premex reactor ag
fax	industriestrasse 11
internet	ch-2543 lengnau/switzerland
e-mail	+41 (0)32 653 60 20
	+41 (0)32 653 60 25
	www.premex-reactorag.ch
	office@premex-reactorag.ch

h p m sonar

