

《 COMMODITY DESCRIPTION 》

카다로그 번호	품목번호	품목 및 규격	단위	수량
Cat. No	Item No	Description	Unit	Quantity
R07-91-101	LRG0560	Laboratory Refrigerator (Glass Door type)	set	1

A. Feature

1. Self-Closing Door. 온도 손실을 최소화
2. High Density Polyurethane Form을 사용하여 최상의 단열 효과
3. Forced Air Refrigeration System. 공기 순환 냉각 방식
4. Stable Defrost System. 제상시 온도 변화 최소화
5. 설정 온도의 상하 범위에 대한 알람 설정 가능
6. 레코더를 설치하여 온도 변화 체크 가능 (Option)
7. 슬라이딩 선반 사용 가능 (Option)
8. 도어 오픈 Error 및 Fan 정지 기능으로 온도 변화 최소화
9. 내부 관찰용 LED Lamp 장착
10. Auto Remote Alarm. 알람 발생시 문자나 전화 발송 (option)
11. 제상수 증발 트레이. 제상수의 양이 많을 경우 냉장고 하단에 설치, Heater 내장

B. Specifications


Model		LRG0560
Capacity		560 L
Controller	Control	Digital Control
	Display	GLCD (Graphic LCD)
	Resolution	0.1 °C
Temperature	Range	0 to +10 °C
	Accuracy	±0.3 °C (at 4 °C)
	Uniformity	±1.5 °C (at 4 °C)
Dimension	Interior	w600 × d630 × h1350 mm
	External	w740 × d803 × h1910 mm
Air Circulation		Forced Circulation Type
Defrost		Automatic, Electric Defrost Type
Material	Interior/External	Stainless Steel
	Door	Glass Door (Heat Mirror Film Glass) / Stainless Steel Door
Electric Supply	Power	1 Phase, 220 VAC, 60 Hz
	Power Consumption	292 W/h
Shelf	Wire, Epoxy Coated	3ea
Safety		Door Lock, Over Current Protection, Sensor Error Detection

C. Accessory

1. C07-02-520 / TR2011 / Chart Recorder (옵션)
2. R07-91-805 / LR-LRSH560 / Shelf (옵션)
3. R07-91-825 / LR-LRST560 / Sliding Tray for 560 L (옵션)
4. C07-91-090 / RMAL01 / Auto Remote Alarm (옵션)
5. R07-91-890 / LR-LRDF001 / Defrost tray (옵션)

D. Remark

1. 사용자의 지정장소에 설치 후 1년 동안 무상보증.
2. PL Insurance (제조물배상책임보험)
3. Validation Service (IQ, OQ, PQ)

 www.lklab.com	(주)엘케이랩코리아	전화 : 031-573-4952 팩스 : 031-527-4958	E-mail : info@lklab.com
---	------------	--	----------------------------